

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
22 March 2001 (22.03.2001)

PCT

(10) International Publication Number  
WO 01/19500 A1

- (51) International Patent Classification<sup>7</sup>: B01D 53/94, (72) Inventor; and  
F02M 45/02, F01N 3/20 (75) Inventor/Applicant (*for US only*): TWIGG, Martyn,  
Vincent [GB/GB]; 108 Ermine Street, Caxton, Cambridge  
CB3 8PQ (GB).
- (21) International Application Number: PCT/GB00/03379
- (22) International Filing Date: (74) Agent: WISHART, Ian, Carmichael; Johnson Matthey  
4 September 2000 (04.09.2000) Technology Centre, Blounts Court, Sonning Common,  
Reading RG4 9NH (GB).
- (25) Filing Language: English (81) Designated States (*national*): JP, US.
- (26) Publication Language: English (84) Designated States (*regional*): European patent (AT, BE,  
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,  
NL, PT, SE).
- (30) Priority Data:  
9921376.1 10 September 1999 (10.09.1999) GB Published:  
— With international search report.
- (71) Applicant (*for all designated States except US*): JOHN-  
SON MATTHEY PUBLIC LIMITED COMPANY For two-letter codes and other abbreviations, refer to the "Guid-  
[GB/GB]; 2-4 Cockspur Street, Trafalgar Street, London ance Notes on Codes and Abbreviations" appearing at the begin-  
SW1Y 5BQ (GB). ning of each regular issue of the PCT Gazette.

(54) Title: REGENERATING SULPHUR POISONED DIESEL CATALYSTS

(57) Abstract: A diesel (compression ignition) engine having combustion management means and an exhaust gas aftertreatment system without an NO<sub>x</sub> trap, which system comprising a platinum group metal (PGM) catalyst liable to be poisoned by fuel sulphur to cause significant degradation of catalyst performance, which engine is fuelled, at least intermittently, by a diesel fuel containing such levels of sulphur as to cause poisoning of the catalyst, wherein the combustion management means is effective to modulate the air/fuel ratio ( $\lambda$ ) to 0.90, preferably 0.95, or richer for a time which is in aggregate sufficient to cause release of significant quantities of sulphur-containing species from the catalyst or catalyst components, whereby the catalyst is regenerated.

WO 01/19500 A1